

WHAT IS CLAIMED IS:

1. A variable gain amplifier circuit comprising:

a plurality of variable gain circuits;

a plurality of level detector circuits which detect  
signal levels at respective inputs of said plurality of  
variable gain circuits; and

a plurality of gain control circuits which separately  
control respective gains of said plurality of variable gain  
circuits,

wherein each of said plurality of gain control  
circuits determines a gain to be set therein, based on the  
signal level detected by one which is connected thereto of  
said plurality of level detector circuits and information  
about gain control received from a part or all of other gain  
control circuits existing in its preceding stage or stages.

2. The variable gain amplifier circuit according to claim  
1,

wherein said plurality of level detector circuits are  
connected to said plurality of variable gain circuits,  
respectively, and

wherein said plurality of gain control circuits are  
connected to said plurality of level detector circuits,  
respectively.

3. The variable gain amplifier circuit according to claim  
1, further comprising:

a plurality of filters separately connected to  
respective outputs of said plurality of variable gain  
5 amplifiers; and

a filtered attenuation evaluating circuit which  
evaluates the quantity of signal attenuation by said  
plurality of filters, based on the signal levels detected  
by said plurality of level detector circuits,

10 wherein each of said gain control circuits controls  
the gain of one which is connected thereto of said variable  
gain amplifiers, based on signal attenuation evaluated by  
said filtered attenuation evaluating circuit and the signal  
level detected and output by one which is connected thereto  
15 of said plurality of level detector circuits.

4. The variable gain amplifier circuit according to claim  
1, further comprising:

a plurality of filters separately connected to  
respective outputs of said plurality of variable gain  
5 amplifiers;

an interference attenuation evaluating circuit which  
evaluates the quantity of attenuation of interference  
signals, based on the signal levels detected by said  
plurality of level detector circuits, taking advantage of  
10 idle mode duration; and

an interference attenuation retaining circuit which  
retains a value of attenuation evaluated by said  
interference attenuation evaluating circuit during a  
receiving mode,

15            wherein each of said gain control circuits controls  
the gain of one which is connected thereto of said variable  
gain amplifiers, based on information of the value of  
attenuation of interference signals retained during said  
receiving mode and the signal level detected and output by  
20            one which is connected thereto of said plurality of level  
detector circuits.

5. A receiver circuit comprising:

          a variable gain low-noise amplifier which amplifies  
received high frequency signals;

          a mixer which converts a signal output from said  
5            variable gain low-noise amplifier into an intermediate  
frequency signal;

          a variable gain circuit which amplifies a signal  
output from the mixer;

          a first level detector circuit which detects the  
10            signal level of said variable gain low-noise amplifier;

          a first gain control circuit which controls the gain  
of said variable gain low-noise amplifier;

          a second level detector circuit which detects the  
signal level of said variable gain circuit; and

15            a second gain control circuit which controls the gain  
of said variable gain circuit,

          wherein said first gain control circuit controls the  
gain of said variable gain low-noise amplifier, based on  
the signal level detected by said first level detector  
20            circuit, and supplies information about the gain control

to said second gain control circuit, and

wherein said second gain control circuit controls the gain of said variable gain circuit, based on the signal level detected by said second level detector circuit and  
25 said information about the gain control.

6. The receiver circuit according to claim 5,

wherein said variable gain circuit comprises one or a plurality of variable gain amplifiers and one or a plurality of filters,

5 wherein said second level detector circuit detects signal levels at respective inputs of said variable gain amplifiers, and

wherein said second gain control circuit controls the gain or gains of said one or plurality of variable gain  
10 amplifiers.

7. The receiver circuit according to claim 6,

wherein said first level detector circuit is connected to the inputs of said variable gain amplifiers.

8. The receiver circuit according to claim 5,

wherein said variable gain circuit comprises one or a plurality of variable gain amplifiers and one or a plurality of filters,

5 wherein said second level detector circuit detects signal levels at respective outputs of said variable gain amplifiers, and

wherein said second gain control circuit controls  
respective gains of said variable gain amplifiers.

10

9. The receiver circuit according to claim 5, further  
comprising:

a plurality of filters separately connected to  
respective outputs of said plurality of variable gain  
5 amplifiers; and

a filtered attenuation evaluating circuit which  
evaluates the quantity of signal attenuation by said  
plurality of filters, based on the signal levels detected  
by said plurality of level detector circuits,

10

wherein said gain control circuit controls the  
respective gains of said variable gain amplifiers, based  
on signal attenuation evaluated by said filtered  
attenuation evaluating circuit and the signal levels  
detected and output by said plurality of level detector  
15 circuits.

10. The receiver circuit according to claim 5, further  
comprising:

a plurality of filters separately connected to  
respective outputs of said plurality of variable gain  
5 amplifiers;

an interference attenuation evaluating circuit which  
evaluates the quantity of attenuation of interference  
signals, based on the signal levels detected by said  
plurality of level detector circuits, taking advantage of

10 idle mode duration; and

an interference attenuation retaining circuit which retains a value of attenuation evaluated by said interference attenuation evaluating circuit during a receiving mode,

15 wherein said gain control circuit controls the respective gains of said variable gain amplifiers, based on information of the value of attenuation of interference signals retained during said receiving mode and the signal levels detected and output by said plurality of level  
20 detector circuits.

11. A gain control method for a variable gain amplifier circuit comprising a plurality of variable gain amplifiers, comprising the steps of:

performing gain control of a first stage variable  
5 gain amplifier, based on its output signal level obtained by detecting the signal level at the output of the first stage; and

performing gain control of second stage and  
subsequent variable gain amplifiers from their input signal  
10 levels obtained by detecting the signal levels at the inputs of the variable gain amplifiers and from gain control information obtained at said first stage and at their preceding stage or stages.

12. The gain control method according to claim 11,  
wherein said first stage variable gain amplifier is

a variable gain low-noise amplifier which amplifies received high frequency signals,

5            wherein said variable gain amplifier circuit is a receiver circuit further comprising a mixer which converts a signal output from said variable gain low-noise amplifier into an intermediate frequency signal,

           wherein said second stage variable gain amplifier is  
10        configured to amplify a signal output from said mixer,

           wherein said step of performing gain control of the first stage variable gain amplifier, based on its output signal level obtained by detecting the signal level at the output of the first stage, comprises the step of performing  
15        gain control of said variable gain low-noise amplifier, based on the signal level output from the mixer obtained by detecting the signal level at the output of said mixer,

           wherein said step of performing gain control of second stage and subsequent variable gain amplifiers from  
20        their input signal levels obtained by detecting the signal levels at the inputs of the variable gain amplifiers and from gain control information obtained at said first stage and at their preceding stage or stages comprises the step of performing gain control of said variable gain amplifiers  
25        from their input signal levels obtained by detecting the signal levels at the inputs of the variable gain amplifiers and from gain control information obtained in said variable gain low-noise amplifier and in their preceding variable gain amplifier or amplifiers.